CSCE 531 Spring 2010

Quiz 3

Assigned Monday, 10-01-19

Give a loop invariant for this program fragment: x := 2;i := 1; (*What is the precondition here?*) while (i <= n) do begin x := x*x;i := i+1end

with precondition $n \ge 1$ and postcondition $x = 2^{2^n}$. **Answer:** $x = 2^{2^{i-1}} \land i \le n+1$.

Also answer the following questions.

- 1. What is the precondition before the loop? **Answer:** $x = 2 \land i = 1 \land n \ge 1$
- 2. Your invariant should consist of the conjuction of two formulae. The second formula is: $i \leq n+1$. Why is this formula needed? **Answer:** To insure that i = n + 1 (rather than just i > n) when the loop is exited.
- 3. Show that the precondition at the line with asterisks implies the invariant. **Answer:** In short: (1) Since i = 1 and x = 2, then $x = 2^{2^{i-1}}$. (2) Since i = 1 and $n \ge 1$, then $i \le n + 1$.
- 4. Show that the invariant together with the negation of the loop implies the postcondition. Answer: In short: (1) Since $i \leq n+1$ and i > n then i = n + 1. (2) Since $x = 2^{2^{i-1}}$ and i = n + 1, then $x = 2^{2^n}$.
- 5. Let x be the value of the variable x before executing the body of the loop and x' be the value of the variable x after executing the body of the loop. Write an equation that relates x and x'. **Answer:** x' = x * x.
- 6. Let i be the value of the variable i before executing the body of the loop and i' be the value of the variable **i** after executing the body of the loop. Write an equation that relates i and i'. **Answer:** i' = i + 1.